

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20141222-EX26524  
**Report Reference** EX26524-20141219  
**Issue Date** 2014-DECEMBER-22

**Issued to:** Weifang Juntong Machinery Auxiliaries Co Ltd  
Industrial Park, Gangcheng Street, Hitech Developom  
Weifang  
Shandong 261201 CHINA

**This is to certify that  
representative samples of**

FITTINGS, RUBBER GASKETED  
See Addendum Page

Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.

**Standard(s) for Safety:**

UL 213, Rubber Gasketed Fittings for Fire-Protection  
Service  
ULC/ORD 213, Rubber Gasketed Fittings for Fire-  
Protection Service

**Additional Information:**

See the UL Online Certifications Directory at  
[www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's  
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.

This is to certify that representative samples of the product as specified on this certificate were tested  
according to the current UL requirements.



Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please  
contact a local UL Customer Service Representative at [www.ul.com/contactus](http://www.ul.com/contactus)



# CERTIFICATE OF COMPLIANCE

Certificate Number 20141222-EX26524  
Report Reference EX26524-20141219  
Issue Date 2014-DECEMBER-22

## Coupling

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT1	Rolled	10	1, 1-1/4, 1-1/2, 2, 3, 4, 6	300
XGQT1	Rolled	10	8, 10	232
XGQT1	Rolled, Cut	40	1, 1-1/4, 1-1/2, 2, 3, 4, 6	300
XGQT1	Rolled, Cut	40	8, 10	232
XGQT1	Cut, Rolled	GB/T3091	3OD(76.1mm), 4-1/4OD(108.1mm), 5-1/4OD(133mm), 5-1/2OD(139.7mm), 6-1/4OD(159mm), 6-1/2OD(165.1mm)	300

## Flexible coupling

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT2	Rolled	10	4	300
XGQT2	Rolled	10	8	232
XGQT2	Rolled, Cut	40	4	300
XGQT2	Rolled, Cut	40	8	232
XGQT2	Cut, Rolled	GB/T3091	5-1/2OD(139.7mm) , 6-1/2OD(165.1mm)	300

## Flange Adapter

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT18	Rolled	10	2, 3, 4, 6, 8;	232

*B. Mahlen*

Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at [www.ul.com/contactus](http://www.ul.com/contactus)



# CERTIFICATE OF COMPLIANCE

Certificate Number 20141222-EX26524  
Report Reference EX26524-20141219  
Issue Date 2014-DECEMBER-22

XGQT18	Rolled, Cut	40	2, 3, 4, 6, 8;	232
XGQT18	Cut, Rolled	GB/T3091	3OD(76.1mm), 4-1/4OD(108.1mm), 5-1/4OD(133mm), 5-1/2OD(139.7mm), 6-1/4OD(159mm), 6-1/2OD(165.1mm);	232

**Side Outlet/ Mechanical Tee (for use with grooved end pipe or this manufacturer's grooved end fittings)**

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT3	Grooved	10, 40	2 x 1, 1-1/4, 1-1/2; 3 x 1, 1-1/4, 1-1/2, 2; 4 x 1, 1-1/4, 1-1/2, 2, 3OD(76.1mm); 6 x 1, 1-1/4, 1-1/2, 2, 3OD(76.1mm), 3, 4;	300
XGQT3	Grooved	10, 40	8 x 1, 1-1/4, 1-1/2, 2, 3OD(76.1mm), 3, 4-1/4OD(108.1mm), 4;	232
XGQT3	Grooved	GB/T3091	3OD(76.1mm) x 1, 1-1/4, 1-1/2; 4-1/4OD(108.1mm) x 1, 1-1/4, 1-1/2, 2, 3OD(76.1mm); 5-1/2OD(139.7mm) x 1, 1-1/4, 1-1/2, 2, 3OD (76.1mm), 3; 6-1/2OD(165.1mm) x 1, 1-1/4, 1-1/2, 2, 3OD(76.1mm), 3, 4;	300
XGQT3S	Threaded	10, 40	2 x 1, 1-1/4, 1-1/2; 3 x 1, 1-1/4, 1-1/2, 2; 4 x 1, 1-1/4, 1-1/2, 2, 3OD(76.1mm); 6 x 1, 1-1/4, 1-1/2, 2, 3OD(76.1mm), 3;	300
XGQT3S	Threaded	10,40	8 x 1, 1-1/4, 1-1/2, 2, 3OD(76.1mm), 3, 4;	232
XGQT3S	Threaded	GB/T3091	3OD(76.1mm) x 1, 1-1/4, 1-1/2; 4-1/4OD(108.1 mm) x 1, 1-1/4, 1-1/2, 2, 3OD(76.1mm); 5-1/2OD(139.7mm) x 1, 1-1/4, 1-1/2, 2, 3OD (76.1mm), 3; 6-1/4OD(159 mm) x 1, 1-1/4, 1-1/2, 2, 3OD (76.1mm), 3; 6-1/2OD(165.1mm) x 1, 1-1/4, 1-1/2, 2, 3OD(76.1mm), 3, 4;	300
XGQT3U		10, 40	1 x 1/2, 3/4; 1-1/4 x 1/2, 3/4, 1; 1-1/2 x 1/2, 3/4, 1;	300

*B. Mahlenz*

Bruce Mahlenz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at [www.ul.com/contactus](http://www.ul.com/contactus)





# CERTIFICATE OF COMPLIANCE

Certificate Number 20141222-EX26524  
Report Reference EX26524-20141219  
Issue Date 2014-DECEMBER-22

			2 x 1/2, 3/4, 1;	
XGQT3U		GB/T3091	3OD(76.1mm)x 1/2, 3/4, 1;	300



Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at [www.ul.com/contactus](http://www.ul.com/contactus)

