

Dry Pressure Gauge

PGD-012

PGD-013

Pressure gauge 100mm Face

AS/NZS 1349:1986
License No.
AMI 74976



Details

- Phosphor Bronze Bourbon Tube
- Dual Scale PSI & KPA
- 1.0% Accuracy
- AS/NZS 1349:1986
- Temperature range -40° to 70°
- Bronze Connection Stem,
- Centre Back & Panel Clamp
- American Standard ASME B40.1

100MM face

MODEL	Pressure
PGD-012	∅ - 1600 KPA
PGD-013	∅ - 2500 KPA

Applications Suitable for all gaseous and liquid media that will not obstruct the pressure system or attack copper alloy parts, specially designed for difficult ambient conditions of use, as the rear vibrations or quick changes of pressure, also useful for adverse ambient.

Applications for 111AL

- > Used for pneumatic systems.
- > Compressors, compressed air system
- > Suitable for fluid medium which does not clog connection port or corrode copper alloy.

Case	Black Steel (Black Painting Steel)
Ring	Black Steel (Black Painting Steel)
Window	Glass
Socket & Connection	Brass
Movement	Brass
Bourbon tube	Brass
Pointer and dial	Aluminum
THREAD	3/8 Inch BSP (10mm)
ACCURACY	+/- 1.0%

Operating temperature

Ambient/MEDIA	-40°C to 70°C
----------------------	---------------