

Oil filled pressure Gauge.



100mm glycerin pressure gauges come in a variety of pressures.

PGO -001 PGO-007

Pressure gauge 100mm face

AS/NZS 1349:1986
License No.
AMI 74976



Details

- StainlessSteel Case& Bezel
- PhosphorBronze Bourbon Tube
- Dual Scale PSI & KPA
- Accuracy + - 1.0%
- AS/NZS 1349:1986
- Temperature range 5°C to 55°C
- Bronze Connection
- Stem, Centre Back & Panel Clamp
- American Standard ASME B40.1

AS/NZS 1349:1986
License No. AMI 74976

MODEL	Kpa Pressure
PGO-001	0 – 1600 kpa
PGO-002	0 – 2500 kpa
PGO-003	0 – 4500 kpa
PGO-004	Compound gauge -100/150 kpa
PGO-005	Compound gauge -100/1100 kpa
PGO-006	Compound gauge -100/1600 kpa
PGO-007	Compound gauge -100/2500 kpa
*PGO-015	0-2500 KPA threaded 15 mm

Applications

Suitable for all gaseous and liquid media that will not obstruct the pressure system or attack copper alloy parts, specially designed for difficult conditions of use, as there are vibrations quick change of pressure, also useful for adverse ambient.

Applications for 115AL

- > Used for hydraulic and pneumatic systems.
- > Compressors, compressed air system
- > Suitable for fluid Medium which does not clog connection port or brass.
- > Provides a protection from vibration & pulsation.

Case	304 Stainless steel, polished
Ring	304 Stainless steel, polished
Window	Polycarbonate
Socket & Connection	Brass
Movement	Brass
Bourbon tube	Brass
Pointer and dial	Aluminum
thread	3/8 inch bsp (10mm)
*threaded only for PGO-015	1/2 inch bsp (15mm)
accuracy	1.0%

Operating temperature

Ambient/media -5°C to 55°C