

Global-Mark Pty. Ltd., certify the gas equipment described hereunder complies with standards listed herein and authorises the certificate holder to affix the Global-Mark Certification label to products listed below.

		CERTIF	ICATION AND (CERTIFICATE HOLDER I	DETAILS			
Certificate Holder Name	Ningbo Rian V	alve Co. Ltd		Manufacturer Name				
Address	Jishan, Xidian	Town, Ninghai Co	unty Ningbo	City Zhejiang 315	613 China			
Client ID	104839		7					
Certification and Authorized	GAS-104839-00	01		Scheme	Global-Mark Cer	rtified Gas S	Safety Scheme	
Mark Number								
Certification Standard(s)	AS 4617-2018 N	Manual shut off gas	valves					
Type of Certification	Gas Safety						17	

	CERTIFICATE DATES		
Certificate Issue Date 5/01/2019	Last Update Date	12/12/2019	
Certification Expiry Date 5/01/2024	System 3	3 Approval	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











Model(s) on which the Global-Mark logo may be applied by the certificate holder as a declaration of compliance by the certificate holder. In placing the authorised mark on the product, the certificate holder makes a declaration of compliance with the certification standard(s) and confirms that the product is identical to the product certified herein. In issuing this Certificate, Global-Mark has relied on the expertise of external bodies (laboratories, and technical experts).

Models listing	5												
Model Number	Model Name	Trade Name	Gas Type	Total Gas Consumption (MJ/hr)	Flame Supervision	Ignition	Annual Energy Consumption (MJ)	Star Rating	Pressure (kPa)	Hue Type	Installation	Options/ Variants	Date Approved

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











286W-08	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Lever handle, Nickel	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	plated or Brass body, Size:	
	Ball Valves	WATTS	TG									8mm.	
						7						Temperature range 0-50	
												deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
			11	7					_ A		100	manufacturers installation	
				1								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











286W-10	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Lever handle, Nickel	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	plated or Brass body, Size:	
	Ball Valves	WATTS	TG									10mm.	
						7						Temperature range 0-50	
												deg C, End fittings	
												covered by this	***
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
				7							100	manufacturers installation	
				1								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











286W-15	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Lever handle, Nickel	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	plated or Brass body, Size:	
	Ball Valves	WATTS	TG									15mm.	
						7						Temperature range 0-50	
												deg C, End fittings	
												covered by this	***
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
				7							100	manufacturers installation	
				1					- 4			requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











20 (111 20	D D II I	DIAM MDC	NG IDG	1 374	N.T.A.	27.4	274		2500		FEI 1	FOF I I II MILI	E (01 (2010
286W-20	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Lever handle, Nickel	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,								connection	plated or Brass body, Size:	
	Ball Valves	WATTS	TG									20mm.	
												Temperature range 0-50	
												deg C, End fittings	61
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					100							relevant installation	
											All	standards (eg	
											A	AS/NZS5601), pipe	
				7							A	manufacturers installation	
				70								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











206111.25	D D 1: 1	DIANI MDC	NG IDC	N.T.A	N.T.A	N.T.A	NIA	NIA	2500	NIA	701 1	FOF I I II N: I I	F (01 (2010
286W-25	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Lever handle, Nickel	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,								connection	plated or Brass body, Size:	
	Ball Valves	WATTS	TG									25mm.	
						1						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
										_	A	standards (eg	
				191							A	AS/NZS5601), pipe	
				7							(A)	manufacturers installation	
				1								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











286W-32	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Lever handle, Nickel	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	plated or Brass body, Size:	
	Ball Valves	WATTS	TG									32mm.	
						7						Temperature range 0-50	
												deg C, End fittings	
												covered by this	***
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
				7								manufacturers installation	
				1								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











286W-40	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Lever handle, Nickel	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	plated or Brass body, Size:	
	Ball Valves	WATTS	TG									40mm.	
						7						Temperature range 0-50	
												deg C, End fittings	
												covered by this	***
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
			11	7					_ A		100	manufacturers installation	
				1							1	requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











					1								
286W-50	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Lever handle, Nickel	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	plated or Brass body, Size:	
	Ball Valves	WATTS	TG	4								50mm.	
						7						Temperature range 0-50	
												deg C, End fittings	
												covered by this	-3
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
											All	standards (eg	
											A 100	AS/NZS5601), pipe	
			4								100	manufacturers installation	
												requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











286WA-08	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Butterfly handle,	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	Nickel plated or Brass	
	Ball Valves	WATTS	TG			7						body, Size: 8mm.)
												Temperature range 0-50	8
						7						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
											All	standards (eg	
											/	AS/NZS5601), pipe	
			4								A	manufacturers installation	
									- 4		A	requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Butterfly handle,	5/01/2019
Manual Isolating	REFLEX,	SNG, TLP,		6	7					connection	Nickel plated or Brass	
Ball Valves	WATTS	TG										
												1
					1							
											relevant installation	
										A	standards (eg	
										A 100	AS/NZS5601), pipe	
								A		A Company	manufacturers installation	
										A	requirements.	
	Manual Isolating	Manual Isolating REFLEX,	Manual Isolating REFLEX, SNG, TLP,	Brass Bodied, RIAN, MRC, NG, LPG, NA	Brass Bodied, RIAN, MRC, NG, LPG, NA	Brass Bodied, RIAN, MRC, NG, LPG, NA NA NA NA NA NA 2500 Manual Isolating REFLEX, SNG, TLP,	Brass Bodied, RIAN, MRC, NG, LPG, NA NA NA NA NA NA 2500 NA Manual Isolating REFLEX, SNG, TLP,	Brass Bodied, Manual Isolating REFLEX, SNG, TLP, NA NA NA NA NA NA NA NA Thread connection	Brass Bodied, Manual Isolating Ball Valves REFLEX, WATTS RIAN, MRC, REFLEX, SNG, TLP, Nickel plated or Brass body, Size:10mm. Temperature range 0-50 deg C, End fittings covered by this certification are required to comply with the applicable standard for the connection type, including pressure limitations, relevant installation standards (eg AS/NZS5601), pipe manufacturers installation			

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











2061114 15	D D 1: 1	DIAM MDC	NG IDC	N.T.A	N.T.A	N.T.A.	NIA	NIA	2500	N.T.A	701 1	FOF D (I I II	E /01 /2010
286WA-15	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Butterfly handle,	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,		8						connection	Nickel plated or Brass	
	Ball Valves	WATTS	TG									body, Size: 15mm.	
				- 4								Temperature range 0-50	
												deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					100							relevant installation	
											Aller	standards (eg	
												AS/NZS5601), pipe	
				7							A 100	manufacturers installation	
				70								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











20.61114 20	D D 1: 1	DIAM MDC	NG IDG	1 374	N.T.A.	27.4	274		2500		m 1	F0 F D (I 1 11	E (01 (2010
286WA-20	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Butterfly handle,	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,								connection	Nickel plated or Brass	
	Ball Valves	WATTS	TG									body, Size: 20mm.	
												Temperature range 0-50	
						7						deg C, End fittings	
						7						covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					100							relevant installation	
											Aller	standards (eg	
												AS/NZS5601), pipe	
				7							A 100	manufacturers installation	
				70								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











2061114 25	D D 1: 1	DIAM MDC	NG IDC	N.T.A	N.T.A	N.T.A	NIA	N.T.A	2500	NT A	701 1	FOF D (I I II	F /01 /2010
286WA-25	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Butterfly handle,	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,		8						connection	Nickel plated or Brass	
	Ball Valves	WATTS	TG									body, Size: 25mm.	
												Temperature range 0-50	
						7						deg C, End fittings	60
						7						covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
											A 1	standards (eg	
												AS/NZS5601), pipe	
			6	7					_ A		A 100	manufacturers installation	
				10								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











											_		
286WS-08	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Locking device	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	handle, Nickel plated or	
	Ball Valves	WATTS	TG									Brass body, Size: 8mm.	
						7						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	**
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
			4	7					_ A		100	manufacturers installation	
				1							100	requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











20.07770.40	B B 1: 1	B1111 1/B C	110 150		4						1	I === - 1. 1 .	F (04 (2040
286WS-10	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Locking device	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	handle, Nickel plated or	
	Ball Valves	WATTS	TG									Brass body, Size: 10mm.	
						-						Temperature range 0-50	
												deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
										_	A	standards (eg	
				150								AS/NZS5601), pipe	
				7					_ A		A 100	manufacturers installation	
				1								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











286WS-15	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Locking device	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	handle, Nickel plated or	
	Ball Valves	WATTS	TG									Brass body, Size: 15mm.	
						7						Temperature range 0-50	
												deg C, End fittings	
												covered by this	***
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					7							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
			11	7					_ A		100	manufacturers installation	
									- 4		A	requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











20 (1110, 20	D D II I	DIANI MDC	NG IDG	1 374	N.T.A.	27.4	274		2500		m 1	FOF I I I	E (01 (2010
286WS-20	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Locking device	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,		8						connection	handle, Nickel plated or	
	Ball Valves	WATTS	TG									Brass body, Size: 20mm.	
						1						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
											A	relevant installation	
										_	A	standards (eg	
				191							A	AS/NZS5601), pipe	
				7							(A)	manufacturers installation	
				No.								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











286WS-25	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Locking device	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,								connection	handle, Nickel plated or	
	Ball Valves	WATTS	TG									Brass body, Size: 25mm.	
												Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
			11	7					_ A		100	manufacturers installation	
				1								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











286WS-32	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Locking device	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	handle, Nickel plated or	
	Ball Valves	WATTS	TG									Brass body, Size: 32mm.	
						7						Temperature range 0-50	
												deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
											All	standards (eg	
											//	AS/NZS5601), pipe	
			4	7					A			manufacturers installation	
									- 4		12	requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











286WS-40	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Locking device	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	handle, Nickel plated or	
	Ball Valves	WATTS	TG									Brass body, Size: 40mm.	
						7						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
			11	7					_ A		100	manufacturers installation	
				1								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











2001110 50	D D 1: 1	DIANI MDC	NC IDC	NT A	NIA	NT A	NIA	N.T.A	2500	NIA	T1 1	F0 F I 1: 1 :	F /01 /2010
286WS-50	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	F&F, Locking device	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,								connection	handle, Nickel plated or	
	Ball Valves	WATTS	TG									Brass body, Size: 50mm.	
						1						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
											A	relevant installation	
										_	A	standards (eg	
				191							A	AS/NZS5601), pipe	
				7					_ A		(A)	manufacturers installation	
				1								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











													100
287W-08	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Lever handle,	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,								connection	Nickel plated or Brass	
	Ball Valves	WATTS	TG									body, Size: 8mm.	
												Temperature range 0-50	
						1						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
			4	3					_ A		100	manufacturers installation	
											A**	requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











													100
287W-10	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Lever handle,	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	Nickel plated or Brass	
	Ball Valves	WATTS	TG									body, Size: 10mm.	
						7						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
			4	7					_ A		100	manufacturers installation	
				1							All the second	requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











													100
287W-15	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Lever handle,	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	Nickel plated or Brass	
	Ball Valves	WATTS	TG									body, Size: 15mm.	
						7						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
			*	7							100	manufacturers installation	
				1								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











287W-20	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Lever handle,	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	Nickel plated or Brass	
	Ball Valves	WATTS	TG									body, Size: 20mm.	
						1						Temperature range 0-50	
												deg C, End fittings	
												covered by this	
			1									certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
				7					_ A			manufacturers installation	
				1								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











													100
287W-25	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Lever handle,	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	Nickel plated or Brass	
	Ball Valves	WATTS	TG									body, Size: 25mm.	
						7						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
			11	7					_ A		100	manufacturers installation	
				1								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











207711 22	D D 1: 1	DIANI MDC	NC IDC	NT A	NIA	NT A	NIA	N.T.A	2500	NIA	T1 1	MODI I II	F /01 /2010
287W-32	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Lever handle,	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,								connection	Nickel plated or Brass	
	Ball Valves	WATTS	TG									body, Size: 32mm.	
						1						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
										_	A	standards (eg	
				191							A	AS/NZS5601), pipe	
				7					_ A		(A)	manufacturers installation	
				1								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











287W-40	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Lever handle,	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	Nickel plated or Brass	
	Ball Valves	WATTS	TG									body, Size: 40mm.	
						7						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
			11	7							100	manufacturers installation	
				1					- 4			requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











287W-50	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Lever handle,	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	Nickel plated or Brass	
	Ball Valves	WATTS	TG									body, Size: 50mm.	
						7						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	***
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
				7							A 100	manufacturers installation	
				1					- 4		All the second	requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











287WA-08	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Butterfly handle,	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	Nickel plated or Brass	
	Ball Valves	WATTS	TG									body, Size: 8mm.	
						7						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	***
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
			11	7					_ A		100	manufacturers installation	
				1								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











287WA-10	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Butterfly handle,	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	Nickel plated or Brass	
	Ball Valves	WATTS	TG									body, Size: 10mm.	
						7						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
											All	standards (eg	
											A 1	AS/NZS5601), pipe	
			4	7								manufacturers installation	
											1	requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











287WA-15	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Butterfly handle,	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	Nickel plated or Brass	
	Ball Valves	WATTS	TG									body, Size: 15mm.	
						7						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
			11	7					_ A		100	manufacturers installation	
				1					- 4			requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











205114 20	D D 1: 1	DIANI MDC	NG IDC	N.T.A	N.T.A	N.T.A	NIA	NIA	2500	NIA	701 1	MOED W. C. I. II	E (01 (2010	
287WA-20	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Butterfly handle,	5/01/2019	
	Manual Isolating	REFLEX,	SNG, TLP,		8						connection	Nickel plated or Brass		
	Ball Valves	WATTS	TG									body, Size: 20mm.		
												Temperature range 0-50	7.0	
												deg C, End fittings		1
						7						covered by this		
												certification are required		
												to comply with the		
												applicable standard for the		
												connection type, including		
												pressure limitations,		
					100							relevant installation		
											Aller	standards (eg		
												AS/NZS5601), pipe		
				7							(A)	manufacturers installation		
				70								requirements.		

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











287WA-25	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Butterfly handle,	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	Nickel plated or Brass	
	Ball Valves	WATTS	TG									body, Size: 25mm.	
						7						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	***
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
			11	7					_ A		100	manufacturers installation	
				1					- 4			requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











287WS-08	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Locking device	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	handle, Nickel plated or	
	Ball Valves	WATTS	TG									Brass body, Size: 8mm.	
						7						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
				7					_ A		100	manufacturers installation	
				1								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











287WS-10	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Locking device	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	handle, Nickel plated or	
	Ball Valves	WATTS	TG									Brass body, Size: 10mm.	
						7						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
				7					_ A		100	manufacturers installation	
				1								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











287WS-15	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Locking device	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	handle, Nickel plated or	
	Ball Valves	WATTS	TG									Brass body, Size: 15mm.	
						7						Temperature range 0-50	
												deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
											All	standards (eg	
											A	AS/NZS5601), pipe	
				7					_ A		100	manufacturers installation	
				10								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











2051110 20	D D 1: 1	DIANI MDC	NG IDC	N.T.A	N.T.A	N.T.A	NIA	N.T.A	2500	NT A	m1 1	MOD I I: I :	E (01 (2010
287WS-20	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Locking device	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,		8						connection	handle, Nickel plated or	
	Ball Valves	WATTS	TG									Brass body, Size: 20mm.	
						1						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
										_	A	standards (eg	
				150								AS/NZS5601), pipe	
				7					_ A		A 100	manufacturers installation	
				10								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











					1								
287WS-25	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Locking device	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	handle, Nickel plated or	
	Ball Valves	WATTS	TG									Brass body, Size: 25mm.	
						7						Temperature range 0-50	
												deg C, End fittings	
												covered by this	
				All Indiana								certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
										628	All	standards (eg	
											/	AS/NZS5601), pipe	
			4								100	manufacturers installation	
											At the second	requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











287WS-32	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Locking device	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	handle, Nickel plated or	
	Ball Valves	WATTS	TG									Brass body, Size: 32mm.	
						7						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	***
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
				7					_ A		// C	manufacturers installation	
				77					A			requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











					/								
287WS-40	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Locking device	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,		A Comment of the Comm						connection	handle, Nickel plated or	
	Ball Valves	WATTS	TG									Brass body, Size: 40mm.	
												Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
											All	standards (eg	
											All the second	AS/NZS5601), pipe	
											A	manufacturers installation	
				7/					A			requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











											_		
287WS-50	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Thread	M&F, Locking device	5/01/2019
	Manual Shut-Off	REFLEX,	SNG, TLP,			7					connection	handle, Nickel plated or	
	Isolating Ball	WATTS	TG									Brass body, Size: 50mm.	
	Valves					7						Temperature range 0-50	
						7						deg C, End fittings	
												covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
					300							relevant installation	
											All	standards (eg	
												AS/NZS5601), pipe	
				7					_ A		100	manufacturers installation	
				18								requirements.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











286PEX	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Crimp PEX	Temperature range 0-50	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,								connection	deg C, End fittings	
	Ball Valves	WATTS	TG									covered by this	
						/-						certification are required	
						7						to comply with the	
						7						applicable standard for the	**
												connection type, including	
												pressure limitations,	
												relevant installation	
												standards (eg	
												AS/NZS5601), pipe	
												manufacturers installation	
											/33	requirements.	
											All the second	PEX&PEX, Lever handle,	
				7					_ A		100	Nickel plated or Brass	
				1/					- 4			body, Sizes: 15mm-	
												25mm.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











													100
286PEX-A	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Crimp PEX	Temperature range 0-50	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	deg C, End fittings	
	Ball Valves	WATTS	TG	4								covered by this	
						1						certification are required	
						7						to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
												standards (eg	
												AS/NZS5601), pipe	
												manufacturers installation	
											Attended	requirements.	
												PEX&PEX, Butterfly	
											A	handle, Nickel plated or	
									- 4			Brass body, Sizes: 15mm-	
				No.								25mm.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











286PEX-S	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Crimp PEX	Temperature range 0-50	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,								connection	deg C, End fittings	
	Ball Valves	WATTS	TG									covered by this	
						/						certification are required	
						7						to comply with the	
												applicable standard for the	**
												connection type, including	
												pressure limitations,	
												relevant installation	
												standards (eg	
												AS/NZS5601), pipe	
											A	manufacturers installation	
											All	requirements.	
												PEX&PEX, Locking device	
				7							///	handle, Nickel plated or	
												Brass body, Sizes: 15mm-	
												25mm.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











286FPEX	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Crimp PEX	Temperature range 0-50	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,	9		7					connection	deg C, End fittings	
	Ball Valves	WATTS	TG									covered by this	
												certification are required	
												to comply with the	
						7						applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
					40							standards (eg	
												AS/NZS5601), pipe	
												manufacturers installation	
											A	requirements.	
											A	F&PEX, Lever handle,	
											ATT I	Nickel plated or Brass	
									- 4		All and a second	body, Sizes: 15mm-	
									- 400		A	25mm.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











286FPEX-A	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Crimp PEX	Temperature range 0-50	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,								connection	deg C, End fittings	
	Ball Valves	WATTS	TG									covered by this	
												certification are required	
												to comply with the	
												applicable standard for the	***
												connection type, including	
												pressure limitations,	
												relevant installation	
			//									standards (eg	
												AS/NZS5601), pipe	
											A	manufacturers installation	
										_	A	requirements.	
				100							A 1	F&PEX, Butterfly handle,	
				7					_ A		A 100	Nickel plated or Brass	
				10								body, Sizes: 15mm-	
												25mm.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











286FPEX-S	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Crimp PEX	Temperature range 0-50	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,	9							connection	deg C, End fittings	
	Ball Valves	WATTS	TG									covered by this	
												certification are required	
						1						to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
					40							standards (eg	
												AS/NZS5601), pipe	
												manufacturers installation	
											A	requirements.	
											A 1	F&PEX, Locking device	
					r						A second	handle, Nickel plated or	
									_ A		100	Brass body, Sizes: 15mm-	
												25mm.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











287MPEX	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Crimp PEX	Temperature range 0-50	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,								connection	deg C, End fittings	
	Ball Valves	WATTS	TG									covered by this	
						y-						certification are required	
						7						to comply with the	
												applicable standard for the	
												connection type, including	
												pressure limitations,	
												relevant installation	
			//									standards (eg	
												AS/NZS5601), pipe	
											A	manufacturers installation	
										_	A	requirements.	
											All	M&PEX, Lever handle,	
				7					_ A		A11	Nickel plated or Brass	
												body, Sizes: 15mm-	
												25mm.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











												_	
287MPEX-A	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Crimp PEX	Temperature range 0-50	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	deg C, End fittings	
	Ball Valves	WATTS	TG									covered by this	
						7						certification are required	
						7						to comply with the	
												applicable standard for the	
				All I								connection type, including	
												pressure limitations,	
												relevant installation	
												standards (eg	
												AS/NZS5601), pipe	
												manufacturers installation	
					1					-	All	requirements.	
											A 1	M&PEX, Butterfly handle,	
											100	Nickel plated or Brass	
											100	body, Sizes: 15mm-	
)					A				
												25mm.	

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.











											_	_	
287MPEX-S	Brass Bodied,	RIAN, MRC,	NG, LPG,	NA	NA	NA	NA	NA	2500	NA	Crimp PEX	Temperature range 0-50	5/01/2019
	Manual Isolating	REFLEX,	SNG, TLP,			7					connection	deg C, End fittings	
	Ball Valves	WATTS	TG									covered by this	
						1						certification are required	
												to comply with the	
												applicable standard for the	-0.07
												connection type, including	
												pressure limitations,	
												relevant installation	
												standards (eg	
												AS/NZS5601), pipe	
											A	manufacturers installation	
											All	requirements.	
											//	M&PEX, Locking device	
				7							All lines	handle, Nickel plated or	
				1/2							All and a second	Brass body, Sizes: 15mm-	
												25mm.	

COMMENTS OR CONDITIONS ON THE CERTIFICATION

Temperature range 0-60 deg C

End of document

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.







